Krytox™ GPL 246



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/16/2018

 5.0
 05/29/2018
 1332498-00032
 Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : Krytox™ GPL 246

Product code : D12430492

SDS-Identcode : 130000031516

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19899 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : For professional users only.

Do not use or resell Chemours[™] materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information,

please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Inhalation) : Category 4

Eye irritation : Category 2A

GHS label elements

Hazard pictograms

Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

H332 Harmful if inhaled.

Krytox™ GPL 246



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

Precautionary Statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flulike symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Copper	7440-50-8	>= 10 - < 20

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately., When symptoms persist or in all cases of

doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Krytox™ GPL 246



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

Most important symptoms and effects, both acute and

delayed

Inhalation may provoke the following symptoms:

Irritation Lung edema

Eye contact may provoke the following symptoms

Blurred vision Discomfort Lachrymation

Skin contact may provoke the following symptoms:

Irritation Redness

Causes serious eye irritation.

Harmful if inhaled.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

Specific hazards during fire

ighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Hydrogen fluoride carbonyl fluoride

potentially toxic fluorinated compounds

aerosolized particulates

Carbon oxides Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Krytox™ GPL 246



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/16/2018

 5.0
 05/29/2018
 1332498-00032
 Date of first issue: 02/27/2017

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Advice on safe handling : Do not swallow.

Do not get in eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep container tightly closed.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
		exposure)	concentration	





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02/16/2018

 5.0
 05/29/2018
 1332498-00032
 Date of first issue: 02/27/2017

Copper	7440-50-8	TWA (Dust and mist)	1 mg/m³ (Copper)	ACGIH
		TWA (Fumes)	0.2 mg/m ³ (Copper)	ACGIH
		TWA (Dust)	1 mg/m³ (Copper)	NIOSH REL
		TWA (Mist)	1 mg/m³ (Copper)	NIOSH REL
		TWA (dusts and mists)	1 mg/m³ (Copper)	OSHA Z-1
		TWA (Fumes)	0.1 mg/m ³ (Copper)	OSHA Z-1

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
Hydrofluoric acid	7664-39-3	TWA	3 ppm	NIOSH REL
			2.5 mg/m ³	
		С	6 ppm	NIOSH REL
			5 mg/m ³	
		TWA	3 ppm	OSHA Z-2
		TWA	0.5 ppm	ACGIH
			(Fluorine)	
		С	2 ppm	ACGIH
			(Fluorine)	
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
1			''	
		STEL	5 ppm	ACGIH
		ST	5 ppm	NIOSH REL
			15 mg/m ³	
		TWA	2 ppm	NIOSH REL
			5 mg/m ³	
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
			, "	
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm	OSHA Z-1
			9,000 mg/m ³	
		TWA	5,000 ppm	NIOSH REL
			9,000 mg/m ³	
		ST	30,000 ppm	NIOSH REL
			54,000 mg/m ³	
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
			''	
		TWA	35 ppm	NIOSH REL
			40 mg/m ³	
		С	200 ppm	NIOSH REL
			229 mg/m ³	
		TWA	50 ppm	OSHA Z-1
			55 mg/m ³	

Engineering measures

Processing may form hazardous compounds (see section

10).

Krytox™ GPL 246



Version 5.0

Revision Date: 05/29/2018

SDS Number: 1332498-00032 Date of last issue: 02/16/2018 Date of first issue: 02/27/2017

Minimize workplace exposure concentrations.

Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material Chemical-resistant gloves

Remarks Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection Wear the following personal protective equipment:

Safety goggles

Skin and body protection Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures Ensure that eye flushing systems and safety showers are

> located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Grease

Color copper

Odor odorless

Odor Threshold No data available

Krytox™ GPL 246



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

pH : No data available

Melting point/freezing point : 608 °F / 320 °C

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Will not burn

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : 572 °F / 300 °C

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Hazardous decomposition products will be formed at elevated

temperatures.

Krytox™ GPL 246



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

П

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition products

Thermal decomposition : Hydrofluoric acid

Carbonyl difluoride Carbon dioxide Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 3,239 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 4.94 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

Components:

Copper:

Acute oral toxicity : LD50 (Rat): 481 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.733 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Copper:

Species : Rabbit

Method : OECD Test Guideline 404

Krytox™ GPL 246



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Copper:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Copper:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Copper:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Method: Directive 67/548/EEC, Annex V, B.12.

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.





Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Copper:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rabbit

Application Route: Ingestion

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Components:

Copper:

Routes of exposure : inhalation (dust/mist/fume)

Assessment : No significant health effects observed in animals at concentra-

tions of 0.2 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Copper:

Species : Rat

NOAEL : $>= 2 \text{ mg/m}^3$

Application Route : inhalation (dust/mist/fume)

Exposure time : 28 Days

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Copper:

Krytox™ GPL 246



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.068 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): 0.006 mg/l

Exposure time: 48 h

Toxicity to fish (Chronic tox-

icity)

: NOEC (Oncorhynchus mykiss (rainbow trout)): 0.0022 mg/l

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (Copper)

Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Copper)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

956

Packing instruction (passen-

ger aircraft)

956





Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A

EmS Code : F-A, S-F Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Copper)

Class : 9 Packing group : III

Labels : CLASS 9 ERG Code : 171

Marine pollutant : yes(Copper)

Remarks : Above applies only to containers over 119 gallons or 450

liters

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Copper	7440-50-8	5000	33670

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

Serious eye damage or eye irritation

Krytox™ GPL 246



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Copper 7440-50-8 >= 10 - < 20 %

US State Regulations

Pennsylvania Right To Know

PFPE fluid Trade secret
Copper 7440-50-8
Fluoropolymer Trade secret

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California List of Hazardous Substances

Copper 7440-50-8


California Permissible Exposure Limits for Chemical Contaminants

Copper 7440-50-8

SECTION 16. OTHER INFORMATION


Further information

NFPA 704:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Krytox™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors. All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)





Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIH / C : Ceiling limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-2 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 05/29/2018

Krytox™ GPL 246



Version Revision Date: SDS Number: Date of last issue: 02/16/2018 5.0 05/29/2018 1332498-00032 Date of first issue: 02/27/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8