



#### 1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Name: X-P35 Product Use: Cleaning Solvent

### MANUFACTURER/DISTRIBUTOR:

Miller-Stephenson Chemical 55 Backus Ave Danbury, Conn. 06810 USA (203) 743-4447 Emergency Phone Number: (800) 424-9300

### 2. HAZARDS IDENTIFICATION

### Hazard classification

Serious Eye Damage/Irritation: Category 2A.

# Label elements: Signal word

Warning

# Pictogram



#### **Hazard Statements**

Causes serious eye irritation.

# **Prevention Statements**

Wash skin thoroughly after handling.

Wear eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/ container to an approved waste disposal plant.

#### Other Hazards

In use, may form flammable/explosive vapor-air mixture. Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may lead to death without warning symptoms, due to cardiac effects.

#### 3. INGREDIENTS

Material (s)	CAS No.	Approximate %
1,1,1,2,2,3,4,5,5,5-Decafluoropentane	138495-42-8	62 - 68
Isopropyl Alcohol	67-63-0	33 - 37

#### 4. FIRST AID MEASURES

**Inhalation:** Remove patient to fresh air. Get medical attention if symptoms occur.

**Eye:** Flush with large amounts of water for at least 15 minutes, lifting eyelids until no evidence of the chemical remains. Remove contact lenses, if present and easy to do. Continue to rinse. Get medical attention.

Skin: Wash skin with water and soap as precaution. after contact. Get medical attention if symptoms occur.

**Oral:** DO NOT induce vomiting without medical advice. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed: May cause cardiac arrhythmia.

Skin contact may provoke the following symptoms: Dermatitis, Irritation, Discomfort, Pain, Redness, Rash, Itching, Swelling of tissue, Superficial burning sensation

Eye contact may provoke the following symptoms: Pain, Tearing, Swelling of tissue, Redness, Impairment of vision Inhalation may provoke the following symptoms: Unconsciousness, Drowsiness, Lack of coordination, Confusion, Dizziness, Central nervous system depression

Effects of breathing high concentrations of vapor may include: Tiredness, Drowsiness, Central nervous system effects, Convulsions Adverse effects from repeated inhalation may include central nervous system effects

Aspiration may cause pulmonary edema and pneumonitis.

Causes serious eye irritation.

Notes to Physician: Treat symptomatically and supportively.

#### 5. FIRE FIGHTING MEASURES

Flash Point: None Method: TCC

Suitable Extinguishing Media: Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO2)

Unsuitable extinguishing media: None known.

**Specific hazards during fire-fighting:** Vapors may form explosive mixture with air. Exposure to combustion products may be hazardous to health. Hazardous combustion products: Hydrogen fluoride, Carbonyl fluoride, Carbon oxides.

**Specific extinguishing methods:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Evacuate personnel to safe areas. Cool containers with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Evacuate area.

**Special fire-fighting protective equipment:** In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

#### 6. ACCIDENTAL RELEASE MEASURES

**Safeguards (Personnel):** Evacuate personnel to safe area. Ventilate area, especially low or enclosed places where heavy vapors might collect. In case of insufficient ventilation, wear suitable respiratory equipment.

**Environmental precautions:** Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g.by containment or barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**Spill Cleanup**: Contain spillage, and then collect with inert absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

### 7. HANDLING AND STORAGE

**Handling:** Use in a well-ventilated area to avoid breathing vapors. Vapors are heavier than air and accumulate in low areas. Use only with adequate ventilation. Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential. Do not eat, drink, or smoke. Do not swallow. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

**Storage Conditions**: Store tightly sealed in a clean, dry place, and well-ventilated place. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Do not store in temperatures that exceed 125°F/52°C, because the containers could leak or rupture from pressure and expansion. Take care to prevent spills, waste and minimize release to the environment.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:	TLV (ACGIH)	PEL (OSHA
1,1,1,2,2,3,4,5,5,5-Decafluoropentane	None Established	None Established
Isopropyl Alcohol	400 ppm, STEL	400 ppm, 8 Hr. TWA

Respiratory Protection: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection

Eye Protection: Avoid eye contact. Use chemical goggles or safety glasses with side shields.

**Skin Protection:** Avoid contact with skin. Use gloves impervious to this material (eg. Viton) when prolonged or frequently repeated contact occurs. For special applications, we recommend clarifying the resistance to chemicals of the afore mentioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point:** 128°F/53°C Approx **Percent Volatile by Volume:** 100

**Vapor Density (Air=1):** >1 **Solubility in H<sub>2</sub>O:** Partly miscible with water.

pH Information: Neutral Evaporation Rate (CC14=1): N.A.

Form: Liquid Appearance: Clear & Colorless

Color: Colorless Odor: Faint alcohol odor

### 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Vapors may form flammable mixture with air. In use may form flammable/explosive vapor-air

mixture.

Material and Conditions to Avoid: None known.

Hazardous decomposition products: No hazardous decomposition products are known.

### 11. TOXICOLOGICAL INFORMATION

### 1,1,1,2,2,3,4,5,5,5-Decafluoropentane

Information on likely routes of exposure: Inhalation, Skin contact, Ingestion, Eye contact

Acute Toxicity: Not classified based on available information.

Skin Corrosion/Irritation: Not classified based on available information.

Serious Eye Irritation/ Eye Irritation: Not classified based on available information.

**Skin Sensitization:** Not classified based on available information. **Respiratory Sensitization:** Not classified based on available information

**Germ Cell Mutagenicity:** Not classified based on available information. **Carcinogenicity:** Not classified based on available information.

**Reproductive toxicity:** Not classified based on available information. **STOT-single exposure:** Not classified based on available information. **STOT-repeated exposure:** Not classified based on available information.

Aspiration toxicity: Not classified based on available information.

## Isopropyl Alcohol

**Acute Toxicity** 

Oral: LD50, Rat, >5,000 mg/kg

**Skin Absorption:** LD50, Rat, >5,000 mg/kg **Inhalation:** LC50, 6 h, Vapor, Rat, >25 mg/l

Skin Corrosion/Irritation: No skin irritation in rabbits.

Serious Eye Damage/Irritation: Irritation to eyes in Rabbits, reversing within 21 days.

**Skin Sensitization:** Not classified based on available information. **Respiratory Sensitization:** Not classified based on available information.

**Germ Cell Mutagenicity:** In vitro and In vivo - Not Mutagenic **Carcinogenicity:** Negative based in inhalation testing in rats.

Reproductive Toxicity: Not classified based on available information.

STOT- single exposure: May cause drowsiness or dizziness

STOT- repeated exposure: Not classified based on available information. Aspiration toxicity: Not classified based on available information.

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

#### 1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Ecotoxicity: No data available

**Persistence and degradability:** No data available **Bioaccumulative potential:** No data available

Mobility in soil: No data available

Other adverse effects

**Results of PBT and vPvB assessment:** This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This

substance is not considered to be very persistent and very bioaccumulating (vPvB).

### **Isopropyl Alcohol:**

Toxicity to fish: LC50, fathead minnow (Pimephales promelas), 96 h: 9,640 mg/l

Toxicity to daphnia and other aquatic invertebrates: EC50, water flea (Daphnia magna), 24 h: >10,000 mg/l

Toxicity to microorganisms: EC50, (Pseudomonas putida), 16 h: >1,050 mg/l

Persistence and degradability: Rapidly degradable.

Bioaccumlative potential: Partition coefficient: n-octanol/water: log Pow: 0.05

**Mobility in soil:** No data available.

#### 13. <u>DISPOSAL CONSIDERATIONS</u>

If recycling is not practicable, dispose of in compliance with local regulations. Remove to a permitted waste disposal facility. The product should not be allowed to enter drains, water courses or the soil.

### 14. TRANSPORT INFORMATION

U.S. DOT

Not Regulated

**IATA** 

Not Regulated

# **IMDG**

Not Regulated

### 15. REGULATORY INFORMATION

### **U.S. Federal Regulations**

**TSCA:** All ingredients are listed in TSCA inventory.

1,1,1,2,2,3,4,5,5,5-Decafluoropentane (CAS# 138495-42-8) - The United States Environmental Protection Agency has established a Significant New Use Rule (SNUR; 40 CFR 721.5645) for this product. This product contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D.

**CERCLA Reportable Quantity:** This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity:** This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity:** This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards: Serious eye damage or eye irritation.

**SARA 313:** This material contains the following component that is subject to reporting levels established by SARA Title III, Section 313: Isopropyl Alcohol (Propan-2-ol), 67-63-0

#### 16. OTHER INFORMATION

### **NPCA-HMIS Ratings:**

Health - 2 Flammability - 1 Reactivity - 0

Personal Protective rating to be supplied by user depending on the conditions.

#### FOR INDUSTRIAL USE ONLY

### **REVISION DATE: APRIL 2019**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.